


NINGBO BEILUN MEANK MAGNETICS CO.,LTD

Website: www.magnetic-holders.com

E-mail: sales@magnetic-holders.com

Specification of standard ferrite cup magnet with internal(female) threaded screw bushing



Model	Dimension					Pull Force (N)
	D(mm)	d(mm)	H(mm)	h(mm)	M(mm)	
Ferrite-D-10	10	6	11.5	4.5	M3	4
Ferrite-D-13	13	6	11.5	4.5	M3	10
Ferrite-D-16	16	6	11.5	4.5	M3	18
Ferrite-D-20	20	6	13	6.0	M3	30
Ferrite-D-25	25	8	15	7.0	M4	40
Ferrite-D-32	32	8	15	7.0	M4	80
Ferrite-D-36	36	8	16	8.0	M4	10.0
Ferrite-D-40	40	10	18	8.0	M5	125
Ferrite-D-47	47	8	17	9.0	M4	180
Ferrite-D-50	50	12	22	10.0	M6	220
Ferrite-D-57	57	8	18.5	10.5	M4	280
Ferrite-D-63	63	15	30	14.0	M8	350
Ferrite-D-80	80	20	34	18.0	M10	600
Ferrite-D-100	100	22	43	22.0	M12	900
Ferrite-D-125	125	25	50	26.0	M14	1300